

8500AV

Digital Pulse Oximeter

Performance You Can Trust for Veterinary Use

The 8500AV digital handheld pulse oximeter is a universal tool to help you treat your patients with the best possible care. Proven accurate for pulse rates up to 450 beats per minute, the 8500AV is perfect for monitoring during surgeries and dental procedures. And, as the industry benchmark for durability and performance, this oximeter has gained the confidence of veterinary professionals worldwide. The versatility of the 8500AV makes it a cost-effective solution for all monitoring and research applications.



Product Highlights

- » **Easy-to-Use** – Bright LED display
- » **Indication of Pulse Quality** – Tricolor perfusion indicator
- » **Reliable** – Proven NONIN digital pulse oximetry technology
- » **Efficient** – 100 hours of battery life
- » **Durable** – Extremely rugged construction
- » **Compatible** – Works with NONIN's complete line of PureLight® Vet sensors

Pure Functionality

The 8500AV has an audible pulse indicator and large LED displays that are visible in low-light situations. The tricolor perfusion indicator provides immediate feedback to assess pulse quality. This information is useful to determine if repositioning of the sensor is necessary and requires little training to interpret.

Alarm Functions

- » SpO₂ High/Low
- » Pulse Rate High/Low
- » Audible Mute
- » Audible Disable



Sensors

NONIN's PureLight Vet sensors produce the pure light spectrum which eliminates variations in readings from patient-to-patient and sensor-to-sensor. NONIN's PureLight sensors deliver the outstanding performance you need to get the job done.



2000SL – Clip on sensor for tongue applications, paw pads and well-vascularized areas.



2000T – For placement on the underside base of the tail or other well vascularized surfaces.



2000SA – Wrap sensor for placement on the toe (large animal) or base of the tail or foot (small animal).

Specifications

Dimensions	8 cm (3") W x 15 cm (6") H x 2 cm (1") D
Weight	280 g (10 oz) with batteries
Warranty	3 years
Oxygen Saturation Display Range	0–100% SpO ₂
Pulse Rate Display Range	18–450 beats per minute (BPM)
Accuracy^a	
Oxygen Saturation (%SpO ₂ ±1 SD) ^b :	70–100% ±2 digits
Pulse Rate:	±3% ±1 digit
Measurement Wavelengths	
Red:	660 nanometers
Infrared:	925 nanometers
Indicators	
Pulse Quality Display:	Tricolor LED segments
Numeric Displays:	Two 3-digit 7-segment LEDs
Temperature (Operating)	-20° to +50°C (-4° to +122°F)
Storage:	-30° to +50°C (-22° to +122°F)
Humidity (Operating)	10–90% noncondensing
Storage:	10–95% noncondensing
Power Requirements	6AA alkaline batteries, 100 hours typical operation

Classifications per IEC 60601-1 / UL60601-1


Type of Protection:	Internally powered (on battery power)
Degree of Protection:	Type BF-Applied Part
Mode of Operation:	Continuous

^aAccuracy is specified for adult human hemoglobin measure at the fingertip. Although animal hemoglobin has similar optical characteristics, the other types of hemoglobin may affect accuracy.

^b±1 Standard Deviation encompasses 68% of the population.

Quality Systems are registered to ISO 13485:2003 and EC certificates per Annex II, clause 3 of EC Directive No. 93/42/EEC concerning medical devices.

Specifications are subject to change without notice.



Your Partner of Choice. With more than 20 years of experience and dedication to the design and support of noninvasive monitoring devices, NONIN has helped many medical professionals meet clinical and economic objectives. Trusted by clinicians worldwide, countless tests are performed every day on thousands of NONIN pulse oximeters in more than 125 countries. NONIN's dedication to technological leadership, precision manufacturing and uncompromised customer support ensures quality products and service you expect.

Authorized Distributor:



Ph: 800.211.0036

Fx: 888.729.9010

www.apexx360.com



Nonin Medical, Inc.

13700 1st Avenue North
Phone: +1.763.553.9968
Fax: +1.763.577.5521

Plymouth MN 55441-5443, USA
Toll Free: 800.356.8874
Email: info@nonin.com